

BRISA & BRISA PLUS series

van Elewout
Kompressoren

Dobbeweg 3B
2254 AG Voorschoten
www.elewout.nl
+31(0)71-561 84 68

Soundproofed compressors of easy mounting and installation. Simply plug in and operate. These require low maintenance and are ideal for urban areas where noise can be an inconvenience to neighbors, or in areas where you don't have a specific site for the compressor and noise can be a problem.

Availability of special anti-dust filters
(quarries, cement, etc.).



BRISA 310 PLUS

SOUNDPROOFED PISTON COMPRESSORS / 23

Features

- CLASSIC series head.
- **ARRIVAL:** Fan pulleys of injected aluminum with Double Wind Geometry- NACA profile that provide a 28% increase in head cooling.
- ELECTRIC MOTOR low power consumption and high performance. Service S1.
- AIR TANK of 90 liters capacity (50 liters models up to 3 HP).
- Economic maintenance.
- PLUG & PLAY, simple installation, plug in and operate.
- Special ANTIVIBRATION rubbers.
- FAN for heat evacuation.
- Analog HOURMETER.
- RELAY of direction of rotation.
- Condensation DRAIN.
- AFTERCOOLER for optimal ventilation of the compressor.
- Maintenance LED (models of 4 and 5,5 HP).
- OIL-LESS INDICATOR LED (models of 4 and 5,5 HP)

Only
BRISA PLUS
series

- Tanks are manufactured according to EU directives 2014/29/EU and 2014/68/EU.

- In the case of a complete installation of a compressor with air treatment, the system would consist of BRISA PLUS compressor, particle separator filter series FEP and refrigerant dryer series EDS (or REDE if BRISA series).

Air flow is set according to ISO 1217.

Noise level as CAGI PNEUROP- measured in the open air, at a distance of 1 meter.



BRISA SERIES

Code	Model	HP	Kw	Ph	Lts	Cyl./St.	l/m	m³/h	r.p.m.	dB (A)	LxWxH mm	Kg
5088141	BRISA 310M	2	1,5	1	50	2/1	310	18,6	920	61	740x465x970	112
5188143	BRISA 310	2	1,5	3	50	2/1	310	18,6	1135	61	740x465x970	11
5098141	BRISA 400M	3	2,2	1	50	2/2	400	24	920	65	740x465x970	12
5198143	BRISA 400	3	2,2	3	50	2/2	400	24	1135	65	740x465x970	127



BRISA 310



BRISA 310 PLUS



BRISA PLUS SERIES

10 BAR

Code	Model	HP	Kw	Ph	Lts	Cyl./St.	l/m	m³/h	r.p.m.	dB (A)	LxWxH mm	Kg
5088144	BRISA 310M PLUS	2	1,5	1	50	2/1	310	18,6	920	61	740x465x970	112
5188145	BRISA 310 PLUS	2	1,5	3	50	2/1	310	18,6	1135	61	740x465x970	112
5198145	BRISA 400 PLUS	3	2,2	3	50	2/2	400	24	1135	65	740x465x970	127



15 BAR

Code	Model	HP	Kw	Ph	Lts	Cyl./St.	l/m	m³/h	r.p.m.	dB (A)	LxWxH mm	Kg
5208173	BRISA 590 PLUS	4	3	3	90	2/2	590	35,4	910	64	1020x705x1185	174
5218173	BRISA 780 PLUS	5,5	4	3	90	2/2	780	46,8	1085	64	1020x705x1185	180



Compressors, whose maximum working pressure is 10 bar, are preset with a minimum standard pressure of 6 bar and maximum of 8 bar. Compressors, whose maximum working pressure is 15 bar, are preset with a minimum standard pressure of 10 bar and maximum of 12 bar.