

**van Elewout  
Kompressoren**

Dobbeweg 3B  
2254 AG Voorschoten

www.elewout.nl  
+31(0)71-561 84 68

**Gardner  
Denver**

# Premium compressor design & industry leading warranty

22 to 30 kW  
Fixed Speed & Variable Speed

**iConn**  
by Gardner Denver

**PROTECT** **10**  
years  
Extended Warranty for GD Compressors

Reliability & efficiency  
without compromise





## Reliability. Performance. Value.

### The ESM and VS Series from Gardner Denver

Well known in the industry for quality and reliability, Gardner Denver continuously develops the ESM and VS Series achieving cutting edge performance and efficiency. The ESM23-29 range of lubricated screw compressors comprises of fixed speed and regulated speed (VS) models.

- ▶ **Pressure range**  
5 to 13 bar
- ▶ **Volume flow**  
0.92 to 5.52 m<sup>3</sup>/min
- ▶ **Motor power**  
22 to 30 kW



**GERMAN**   
**ENGINEERING**  
**DESIGN&MANUFACTURE**

### Engineering excellence

Compressors are more than just a financial investment, they are a key component in ensuring that manufacturers, processors and operators receive consistent, high quality low cost air.

The screw compression element is the heart of the compressor and therefore Gardner Denver keeps the design and manufacture in-house, using the latest CNC rotor grinding machinery, coupled with online laser technology.

The resulting reliability and performance ensure that operating costs will remain low throughout the compressors life.


### Premium efficiency airend

The high output airend with slow rotational speed reduces energy costs. In addition to this, the innovative design of the fail safe shaft seal, integrated oil filter and oil regulation valve, ensures external hoses are reduced to a minimum to guarantee the highest levels of quality and reliability are achieved. With the new extended Protect 10 warranty, the airends are covered up to 10 years or 44,000 hours.\*



\*whichever is soonest.





“Gardner Denver lubricated rotary screw compressors incorporate **the very latest technological advances** and guarantee a continuous supply of high quality compressed air.”

A design concept **based on quality**

**Large surface after cooler**

Optimum cooling to ensure low operating and discharge temperatures.

**High performance separator filter**

Two stage filtration ensures highest quality air is delivered to your system (< 3ppm oil carryover). The vessel has a hinged cover for easy maintenance.

**High efficiency electric motor**

The compressors are equipped with an energy saving IE3 electric motor with reduced CO<sub>2</sub> emissions.

**Thermostatically controlled motor driven fan**

High efficient and extremely quiet fan, allows compressor operation in the work place, and the use of the maximum duct length without further assistance.


**Highest quality connections**

Solid hoses and pipe connections with viton victaulic couplings increase reliability and are easy to maintain.

## High modern control system

GD Pilot control system for **reliability** and **simplicity of operation**.

The advanced control system ensures reliable operation and protects your investment by continuously monitoring the



operational parameters. The “GD PILOT” controller also has the capability to have programmable inputs and outputs, control additional equipment as well as providing the following features with a clear readable text.

- Discharge/line pressure display
- Oil temperature display
- Total hours run and loaded hours
- Service due indicator
- Enhanced fault log monitor
- Real time clock
- Timer controlled Stop/Start
- Remote Stop Start
- Auto restart on power failure
- Second pressure setting
- Status indication
- RS485 - Modbus RTU





## Variable speed Compressors

### The perfect response to individual air demand

Variable speed compressors from Gardner Denver can efficiently and reliably handle the varying air demand found in most plant air systems.

The annual cost of ownership can be significantly reduced using variable speed technology.



### Tried and tested inverter concept

- Integrated in the electric cabinet
- Protected from dust by replaceable inlet filters
- Maximum reliability from optimised cooling system
- Ensures high availability and long-life

### Gardner Denver VS features are your benefits

The VS Series products are designed to obtain the greatest efficiency across the entire operating range

- **Wide regulation range**  
No cycles means substantial energy savings
- **Perfect motor - drive - airend design**  
High efficiency across broad flow range





## Gardner Denver efficiency upgrades

### Integrated dryer

Complete with a dryer and water separator, both are fitted with zero loss drains, to eliminate expensive air loss and maximise energy efficiency. Thanks to ESD control, the dryer only consumes energy when the system needs compressed air.



### Integrated heat recovery

Significant energy and costs savings can be achieved with Gardner Denver's efficient integrated heat recovery system. It can be either factory fitted or supplied as retrofit kit including all necessary pipe-work and fittings.

## Compressed air purification

A modern production system and process demands increasing levels of air quality. A Gardner Denver compressed air system utilising the latest technology provides an energy efficient solution at lowest life cycle costs.

- Water Cyclone Separator
- Compressed Air Filter
- Condensate Drain Bekomat System
- Compressed Air Refrigerant Dryer
- Heatless Desiccant Dryers
- Heat Regenerative Desiccant Dryers
- Nitrogen Generator
- GD Connect 12 Multi Compressor Controllers



### iConn Industry 4.0 solution

The compressor range ESM23 to ESM29, VS can be upgraded with iConn, the smart proactive real-time monitoring system, which gives you real-time knowledge about the compressed air system. It enables accurate production planning and total peace-of-mind protection, generating insight and statistics that keep you informed on performance, at the same time highlighting potential issues before they become a problem.



## The best investment protection you can get



Extended Warranty for GD Compressors

### 10 Years Warranty!

The Gardner Denver Protect 10 Warranty and Service programmes will protect you up to 44,000 hours/10 years<sup>1</sup>. It is one of the most generous warranties available in the industry affording you total piece of mind.

### Your benefits:

- The Protect 10 warranty is totally free to the compressor owner<sup>2</sup>
- The Gardner Denver authorised service provider will deliver a guaranteed quality of service
- The Protect 10 service agreement underpinning the warranty will enable accurate maintenance, budgeting and cost of ownership
- The use of genuine Gardner Denver parts and lubricants will maximise compressor life and efficiency

<sup>1</sup> Warranty duration is limited to 6 years/44,000 hours on the whole package, 10 years/44,000 hours on the air end. Whichever is the soonest.

<sup>2</sup> subject to Terms & Conditions

### Compact design - easy installation

The small footprint reduces the space required for installation.

### Easy servicing

The design of these packages ensures that the service points are readily accessible. The enclosure side doors are hinged and removable to allow complete access to all service points. The reduced number of moving parts further lowers the maintenance costs.

### Gardner Denver genuine spare parts

#### Enjoy complete peace of mind.

Genuine Gardner Denver parts and lubricants ensure that compressed air plant reliability and efficiency is maintained at the highest standards. Gardner Denver spare parts and lubricants are distinguished by:

- Long service life, even under harshest conditions
- Minimum losses contributing to energy savings
- High reliability improves plant up-time
- Products manufactured with the strictest Quality Assurance Systems





## Technical data

### ESM23 - 29 Fixed Speed Screw Compressors

Gardner Denver model	Nominal Pressure	Drive Motor	FAD <sup>1)</sup>	Noise Level <sup>2)</sup>	Weight	Dimensions L x W x H
	bar g	kW	m <sup>3</sup> /min	dB(A)	kg	mm
ESM23	7.5	22	4.16	67	650	1345 x 880 x 1612
	10		3.45			
	13		2.98			
ESM26	7.5	26	4.84	68	677	1345 x 880 x 1612
	10		4.13			
	13		3.44			
ESM29	7.5	30	5.52	69	681	1345 x 880 x 1612
	10		4.81			
	13		4.12			

### ESM23F - 29F Fixed Speed with Integrated Dryer

Gardner Denver model	Refrigeration dryer	Pressure Dew Point <sup>3)</sup>	Weight	Dimensions L x W x H
	type	°C	kg	mm
ESM23F	F29E	5	840	1675 x 880 x 1612
ESM26F	F29E	5	867	1675 x 880 x 1612
ESM29F	F29E	5	871	1675 x 880 x 1612

### VS23 - 29 Variable Speed Screw Compressors

Gardner Denver model	Nominal Pressure	Drive Motor	FAD <sup>1)</sup> at 7.5 bar g	FAD <sup>1)</sup> at 10 bar g	FAD <sup>1)</sup> at 13 bar g	Noise Level <sup>2)</sup> at 70% Load	Weight	Dimensions L x W x H
	bar g	kW	m <sup>3</sup> /min	m <sup>3</sup> /min	m <sup>3</sup> /min	dB(A)	kg	mm
VS23	5 - 13	22	1.11 - 4.12	1.03 - 3.50	1.35 - 2.89	68	681	1345 x 880 x 1612
VS26	5 - 13	26	1.11 - 4.78	1.03 - 4.10	0.92 - 3.56	69	708	1345 x 880 x 1612
VS29	5 - 13	30	1.11 - 5.41	1.03 - 4.50	0.92 - 3.82	69	712	1345 x 880 x 1612

### VS23F - 29F Variable Speed with Integrated Dryer

Gardner Denver model	Refrigeration dryer	Pressure Dew Point <sup>3)</sup>	Weight	Dimensions L x W x H
	type	°C	kg	mm
VS23F	F29E	5	871	1675 x 880 x 1612
VS26F	F29E	5	898	1675 x 880 x 1612
VS29F	F29E	5	902	1675 x 880 x 1612

<sup>1)</sup> Data measured and stated in accordance with ISO 1217, Edition 4, Annex C and Annex E and the following conditions: Air Intake Pressure 1 bar A, Air Intake Temperature 20°C, Humidity 0 % (Dry).

<sup>2)</sup> Measured in free field conditions in accordance with ISO 2151, tolerance ± 3dB (A).

<sup>3)</sup> Data refer to ISO 7183, working pressure of 7 bar, inlet temperature 35°C and ambient temperature 25°C.



## Global Expertise

The GD rotary screw compressor range from 2.2 – 500 kW, available in both variable and fixed speed compression technologies, are designed to meet the highest requirements which the modern work environment and machine operators place on them.



The oil-free EnviroAire range from 15 – 315 kW provides high quality and energy efficient compressed air for use in a wide range of applications. The totally oil-free design eliminates the issue of contaminated air, reducing the risk and associated cost of product spoilage and rework.



A modern production system and process demands increasing levels of air quality. Our complete **Air Treatment Range** ensures the highest product quality and efficient operation.



Compressor systems are typically comprised of multiple compressors delivering air to a common header. The combined capacity of these machines is generally greater than the maximum site demand. To ensure the system is operated to the highest levels of efficiency, the **GD Connect** air management system is essential.



**van Elewout  
Kompressoren**

Dobbeweg 3B  
2254 AG Voorschoten

www.elewout.nl  
+31(0)71-561 84 68

gdcompressors.eu@gardnerdenver.com  
[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)

For additional information please contact Gardner Denver or your local representative.

Specifications subject to change without notice.